//product info

// COMPACT FLASH UNITS



INTEGRA 500 PLUS

Code no. 8815FM

// Very short flash duration up to 1/1,390 s and fast flash sequences from 0.5 s
// Adjustable 6 f-stop power range in 1/10 f-stops
// Reflector quick-change automatic for tools with EH connector (10 cm)
// Integrated radio remote receivers – Strobe Wizard Plus and freemask
// Bright 300 W halogen modeling light
// Aluminum drawn cased housing (2.6 mm thick)
// Power regulation in 1/10 f-stops
// Integrated Strobe Wizard Plus and freemask radio receiver
// Remote controlled: power adjustment, flash release, modeling light, stand-by
// Large 7 segment power display
// Digital rotary switches with notch stops and no final stop position
// Active cooling with silent fan
// Multivoltage (110 – 240V)
// Reflector quick-change automatic for tools with EH connector (10 cm)
// Automatic modeling light stand-by mode
// Pluggable flash tube
// Plug-in glass cover
// APD, internal power dump when power is reduced
// Built-in audio and photocell, separately adjustable
// Sync socket for standard 6.3 mm cord
// Test button for manual triggering
// Flash check – visual flash control
// Very low sync voltage to protect digital cameras
// Adjustable panhead
// Built-in protected remote antenna
// Active backlit front panel, ideal for work in the dark
// Bright LEDs show the settings
// Durable foil surface with real buttons. Feel how easy it is to operate
// Accustomed Hensel operation: essentially identical nomenclature and positio ning of switches and controls. Intuitive work, without having to rethink!

TECHNICAL DATA

Rated energy: 500 J
Apertrure from1m (2m),100 ASA, t 1/60, 12" refl.*: 64 8/10 (32 8/10)
Modeling lamp: 300W / G 6,35
Recharging up to min. energy: 0,5 s
Recharging up to max. energy: 1,9 s
Shortest flash duration, t 0,5: 1/1.390 s
Shortest flash duration, t 0,1: 1/470 s
Flash output adjustment in 1/10 stops: 6 f
Output adjustment modeling light: off / full / prop / autored
Remote control: Strobe Wizard Plus, freemask
Modeling light, output adj., test and standby
Weight: 2,87 kg
Dimensions (LxWxH): 33 x 15 x 23 cm

* Values attained with 12" reflector (code no. 9601) for Expert/EH series
Technical data are subject to change. The listed values are guide values and should not be understood as binding in a legal sense. The values can differ due to tolerances in used components.
Values attained at 230 V / 50 Hz voltage. Date of revision: May 2012

HENSEL
PERFORMING LIGHT

HENSEL-VISIT GmbH & Co. KG // Robert-Bunsen-Str. 3 // 97076 Würzburg // Germany
Phone: +49-931-27881-0 // Fax: +49-931-27881-50 // info@hensel.de // www.hensel.de