



NOVA D 2400

Code no. 3624

- // Highly reliable easy operation
- // Fast flash recycling times, max. every 0.35 s and flash durations up to 1/3.160 s
- // Integrated radio remote receivers: Strobe Wizard Plus, freemask and Profoto Air
- Remote controlled: power adjustment, flash release, modeling light, stand-by
- Full remote control compatibility with all manufacturers
- // freemask function: cut-out masks in perfect quality while shooting
- // Symmetrical and asymmetrical power distribution, adjustable 8 f-stop power range in 1/10 f-stops
- // Sockets for **round plugs**
- // Big adjustable 8 f-stop power range
- // Compact, lightweight flash heads with reflector quick-change automatic
- // Capacity regulated power control
- // Unique recharge logic for gentle treatment of the rotating charging capacitors
- // Multivoltage (110 – 230 V) high performance switch power supply
- // Modeling light up to 650 W for each socket: on, off, full, prop, autored
- // Metal housing with sturdy rubber protection profile
- // Unique, easy-to-carry handle with integrated spare fuses
- // Built-in, protected radio antenna in handle
- // Power regulation in 1/10 f-stops
- // 8 f-stop power range
- // Large 7 segment power display
- // Flash check – visual flash control
- // Active cooling with silent fan
- // USB connection for software updates
- // APD, internal power dump when power is reduced
- // Durable foil surface with real buttons. Feel how easy it is to operate.
- // Bright control LEDs show the settings
- // Sync socket for standard 6.3 mm cord
- // Test button for manual triggering
- // Very low sync voltage to protect digital cameras
- // Thermal control of power electronics
- // Accustomed Hensel operation: essentially identical nomenclature and positioning of switches and controls. Intuitive work, without having to rethink!

TECHNICAL DATA

Rated energy: 2400 J
Apertrue from 1m, 100 ASA, t 1/60, 12" refl.*: 180 0/10
Connection: round plug
Recharging up to min. energy: 0,35 s
Recharging up to max. energy: 1,1 s
 Shortest flash duration, t 0,5
 with 1 EH pro Mini: 1/1.450 s
 with 1 EH Pro Mini Speed: 1/3.160 s
Flash output adjustment in 1/10 stops: 8 f
 Output distribution: asymmetrical
Remote control: Strobe Wizard Plus, freemask, Profoto Air
 Modeling light, output adj., test, sync and stand-by
 Weight: 7,8 kg
Dimensions (LxWxH): 26 x 19,5 x 28,3 cm

* Values attained with 12" reflector (code no. 9601) for Expert/EH series
Technical data are subject to change. The listed values are guide values and should not be understood as binding in a legal sense.
The values can differ due to tolerances in used components.
Values attained at 230 V / 50 Hz voltage. Date of revision: May 2012

HENSEL
 PERFORMING LIGHT